

# Non Woven Specifications

## 10 oz. Non Woven Geotextile Fabric

### SPECIFICATIONS

| Property              | Test Method | Roll Value      |
|-----------------------|-------------|-----------------|
| Tensile Strength      | ASTM-D-4632 | 250 lbs.        |
| Elongation            | ASTM-D-4632 | 50%             |
| Trapezoidal Tear      | ASTM-D-4533 | 100 lbs.        |
| CBR Puncture Strength | ASTM-D-6241 | 700 lbs.        |
| AOS                   | ASTM-D-4751 | 100 Sieve       |
| Permittivity          | ASTM-D-4491 | 1.2 Sec-1       |
| Water Flow Rate       | ASTM-D-4491 | 85 gpm/ft.      |
| UV Resistance         | ASTM-D-4355 | 70% / 500 hours |

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. Erosion Control Products offers this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

For more complete information on our products and solutions, visit us on the Web at [www.erosioncontrol-products.com](http://www.erosioncontrol-products.com)

Phone: 1-863-563-3357 | [info@supplysourceusa.com](mailto:info@supplysourceusa.com)

© 2021 ECP. All rights reserved. Terms and conditions apply.

All photos are representative only. Actual products may differ. Materials and specifications are subject to change without notice. Featured products in photos may include additional equipment or accessories.