



Corrugated Steel Water Tanks

Long-Lasting Water Storage

Constructed from high-quality steel, Corrugated Water Tanks are available in a variety of styles and sizes ranging from 720 gallons to 1,100,000 gallons. Known for their durability and strength, Corrugated Bolted Steel Tanks are economical whether for long-term or for temporary liquid storage solutions.

Made from high-strength zinc galvanized carbon steel, corrugated panels are corrosion resistant and provide exceptional strength. Corrugated tanks are custom designed to fit each project's use, as well as for any environmental challenges including sub-zero temperatures, high winds, and even seismic activity. With the 20-year manufacturer's warranty, you can be confident in having long-lasting, quality water storage for many years to come.

Corrugated Steel Water Tanks

A Tank for Many Uses

Standard Features

- Sizes up to 1.1 million gallons
- Tank diameters between 6 ft. and 192 ft.
- High-strength zinc galvanized corrugated carbon steel
- Site specific structural calculations- wet stamped
- Detailed Submittal Drawings

Optional Features

- NSF-61 certified liners and coatings for safe storage of potable water
- Additional liner choices for other liquids
- Powdered coatings available
- Selection of tank colors
- Interior and exterior insulation systems
- Additional fittings and accessories

Benefits

- **Cost Savings.** Benefit from a precision manufacturing process that allows your tank to be built at significant cost savings.
- **Highly Corrosion Resistant.** Zinc panels are galvanized to G115 or G140, providing strength and long-lasting resistance to the elements.
- **Structural Integrity.** Designed to meet current AWWA requirements with ASCE structural codes for water storage tanks (including wind and seismic loading), your tank will be engineered specific to your site and application.
- **Short Lead Time and Simple Installation Process.** Lead times can be as fast as 6-8 weeks for material fabrication. The tanks are designed for easy installation, with light-weight materials, and less equipment needed. Heavy equipment like cranes or booms are not necessary.
- **Long Warranty.** 20-year warranties are provided when installed by manufacturer certified teams, based on application and location.
- **Coatings and Liners.** We have an assortment of coatings and liners available to fit the material use for your corrugated tank, whether Hot Dip Galvanized coatings, powder coatings, or flexible membrane liners. Liners greatly extend the use-life of the tank and provide a second layer of protection. They are designed for easy repair and if needed, inexpensive replacement.
- **USA Made.** Our corrugated tanks are made from US Steel and are manufactured in the United States.



Corrugated Steel Water Tanks

Installation, Warranty & Financing

Full Installation Services

Full installation services are available for customers in the US and Canada. Supervised installations are available for customers outside the US and Canada.

- For commercial size tanks, use a concrete ring beam foundation. Some exclusions apply. Please consult us for more details.
- It is necessary to construct a level area 10-to-13 feet larger than the diameter of the ring beam. The sand inside the ring beam should be a depth of 4 inches and compacted. A clear area of at least 3.3 feet is required all around the tank for construction.
- Site preparation must be completed prior to the arrival of installers.
- For sloping sites, adequate retaining and drainage must be installed prior to completion of the tank construction. Professional engineering advice should be sought on the retaining and drainage requirements.
- Tanks are erected by approved installers on a customer-supplied foundation. A leak test should be done immediately following installation, with the customer supplying the water.



Manufacturer's Warranty

A 20-year manufacturer's warranty on all tanks is available. Just fill out and submit the warranty card as indicated to register your tank.

Easy Financing

We have partnered with JB2 Funding to provide three convenient financing options. Financing and leasing programs are available for new tanks, equipment, machinery, and DOT-compliant water trailers.

Payment Options for Customers in US & Canada:

- Financing
- ACH Deposit/eCheck/Wire Transfer
- Credit Card (Visa, Mastercard, Discover Card)
- Apply for Credit Terms

Our standard policy is to receive payment in advance for any customers without previous purchase history with One Clarion. International customers (including Canada) must pay in advance with SWIFT transfer. Credit card payments must be drawn from a US bank.

Corrugated Steel Water Tanks

Specifications

Corrugated Tank – Roofing Styles

We offer several choices of roof styles for corrugated bolted steel tanks: J-Rib, V-Rib and Flat Seam. Flat roofs are also available on certain models. Ribs are the vertical section that join the roof panels securely to each other. Both styles are fabricated the same way, except for the “bend” in the respective roof ribs, either “J” or “V”. The Flat Seam Roof is only available in models with 6’ or 9’ diameter tanks and a 30° pitched roof.



J-Rib



V-Rib



Flat Seam*

**The J-Rib style requires additional raftering support, where the V-Rib style provides it's own structural support by design.*

Corrugated Tank - 30° Flat Seam Panel

Capacity	Model	Diameter	Radius	Eave Height	Roof Height	Total Height
722 gal	SCT-601-FP	6.2'	3.1'	3.54'	1.41'	4.95'
1,518 gal	SCT-602-FP	6.2'	3.1'	7.08'	1.41'	8.49'
1,624 gal	SCT-901-FP	9.3'	4.6'	3.54'	2.33'	5.87'
2,315 gal	SCT-603-FP	6.2'	3.1'	10.63'	1.41'	12.04'
3,416 gal	SCT-902-FP	9.3'	4.6'	7.08'	2.33'	9.41'
3,111 gal	SCT-604-FP	6.2'	3.1'	14.17'	1.41'	15.58'
3,908 gal	SCT-605-FP	6.2'	3.1'	17.71'	1.41'	19.12'
4,704 gal	SCT-606-FP	6.2'	3.1'	21.25'	1.41'	22.66'
5,208 gal	SCT-903-FP	9.3'	4.6'	10.63'	2.33'	12.96'
7,000 gal	SCT-904-FP	9.3'	4.6'	14.17'	2.33'	16.50'
8,792 gal	SCT-905-FP	9.3'	4.6'	17.71'	2.33'	20.04'
10,585 gal	SCT-906-FP	9.3'	4.6'	21.25'	2.33'	23.58'

Corrugated Steel Water Tanks

Specifications

Corrugated Tank - 10° Low V Rib Roof

Capacity	Model	Diameter	Radius	Eave Height	Roof Height	Total Height
2,886 gal	SCT-1201-LVR	12.4'	6.2'	3.54'	1.60'	5.30'
4,510 gal	SCT-1501-LVR	15.5'	7.7'	3.54'	1.97'	5.51'
6,072 gal	SCT-1202-LVR	12.4'	6.2'	7.08'	1.60'	8.75'
6,494 gal	SCT-1801-LVR	18.6'	9.3'	3.54'	2.29'	5.83'
8,839 gal	SCT-2101-LVR	21.7'	10.8'	3.54'	2.60'	6.13'
9,259 gal	SCT-1203-LVR	12.4'	6.2'	10.63'	1.60'	12.33'
9,488 gal	SCT-1502-LVR	15.5'	7.7'	7.08'	1.92'	9.10'
11,545 gal	SCT-2401-LVR	24.7'	12.4'	3.54'	2.84'	6.38'
12,445 gal	SCT-1204-LVR	12.4'	6.2'	14.17'	1.60'	15.90'
13,663 gal	SCT-1802-LVR	18.6'	9.3'	7.08'	2.29'	9.37'
14,467 gal	SCT-1503-LVR	15.5'	7.7'	10.63'	1.92'	12.63'
14,612 gal	SCT-2701-LVR	27.8'	13.9'	3.54'	3.10'	6.64'
15,631 gal	SCT-1205-LVR	12.4'	6.2'	17.71'	1.60'	19.42'
18,039 gal	SCT-3001-LVR	30.9'	15.5'	3.54'	3.29'	6.83'
18,597 gal	SCT-2102-LVR	21.7'	10.8'	7.08'	2.60'	9.68'
18,817 gal	SCT-1206-LVR	12.4'	6.2'	21.25'	1.60'	22.92'
19,445 gal	SCT-1504-LVR	15.5'	7.7'	14.17'	1.92'	16.17'
20,832 gal	SCT-1803-LVR	18.6'	9.3'	10.63'	2.29'	12.91'
21,828 gal	SCT-3401-LVR	34.0'	17.0'	3.54'	3.90'	7.17'
24,290 gal	SCT-2402-LVR	24.7'	12.4'	7.08'	2.84'	9.92'
24,423 gal	SCT-1505-LVR	15.5'	7.7'	17.71'	1.92'	19.67'
28,001 gal	SCT-1804-LVR	18.6'	9.3'	14.17'	2.29'	16.46'
28,355 gal	SCT-2103-LVR	21.7'	10.8'	10.63'	2.60'	13.22'
29,402 gal	SCT-1506-LVR	15.5'	7.7'	21.25'	1.92'	23.17'
30,742 gal	SCT-2702-LVR	27.8'	13.9'	7.08'	3.10'	10.18'
35,170 gal	SCT-1805-LVR	18.6'	9.3'	17.71'	2.29'	20.00'
35,357 gal	SCT-4301-LVR	43.3'	21.7'	3.54'		8.33'
37,035 gal	SCT-2403-LVR	24.7'	12.4'	10.63'	2.84'	13.47'
37,953 gal	SCT-3002-LVR	30.9'	15.5'	7.08'	3.29'	10.37'
38,112 gal	SCT-2104-LVR	21.7'	10.8'	14.71'	2.60'	16.77'
42,339 gal	SCT-1806-LVR	18.3'	9.3'	21.25'	2.29'	23.54'
45,923 gal	SCT-3402-LVR	34.0'	17.0'	7.08'	3.90'	10.67'

Corrugated Steel Water Tanks

Specifications

46,181 gal	SCT-4901-LVR	49.5'	24.7'	3.54'	7.00'	10.54'
46,872 gal	SCT-2703-LVR	27.8'	13.9'	10.63'	3.10'	13.72'
47,870 gal	SCT-2105-LVR	21.7'	10.8'	17.71'	2.60'	20.31'
49,779 gal	SCT-2404-LVR	24.7'	12.4'	14.17'	2.84'	17.01'
57,866 gal	SCT-3003-LVR	30.9'	15.5'	10.63'	3.29'	13.91'
58,627 gal	SCT-2106-LVR	21.7'	10.8'	31.25'	2.60'	23.85'
62,530 gal	SCT-2405-LVR	24.7'	12.4'	17.71'	2.84'	20.55'
63,002 gal	SCT-2704-LVR	27.8'	13.9'	14.17'	3.10'	17.27'
70,018 gal	SCT-3403-LVR	34.0'	17.0'	10.63'	3.90'	14.60'
74,388 gal	SCT-4302-LVR	43.3'	21.7'	7.08'		11.83'
75,268 gal	SCT-2406-LVR	24.7'	12.4'	21.25'	2.84'	24.09'
77,780 gal	SCT-3004-LVR	30.9'	15.5'	14.17'	3.29'	17.45'
79,132 gal	SCT-2705-LVR	27.8'	13.9'	17.71'	3.10'	20.81'
94,114 gal	SCT-3404-LVR	34.0'	17.0'	14.17'	3.90'	18.06'
95,262 gal	SCT-2706-LVR	27.8'	13.9'	21.25'	3.10'	24.35'
97,159 gal	SCT-4902-LVR	49.5'	24.7'	7.08'	7.00'	14.08'
97,693 gal	SCT-3005-LVR	30.9'	15.5'	17.71'	3.29'	21.00'
113,418 gal	SCT-4303-LVR	43.3'	21.7'	10.63'		15.38'
117,607 gal	SCT-3006-LVR	30.9'	15.5'	21.25'	3.29'	24.54'
118,209 gal	SCT-3405-LVR	34.0'	17.0'	17.71'	3.90'	21.29'
142,304 gal	SCT-3406-LVR	34.0'	17.0'	21.25'	3.90'	24.66'
148,138 gal	SCT-4903-LVR	49.5'	24.7'	10.63'	7.00'	17.63'
152,449 gal	SCT-4304-LVR	43.3'	21.7'	14.17'		18.92'
191,479 gal	SCT-4305-LVR	43.3'	21.7'	17.71'		22.46'
199,117 gal	SCT-4904-LVR	49.5'	24.7'	14.17'	7.00'	21.17'
230,510 gal	SCT-4306-LVR	43.3'	21.7'	21.25'		26.00'
250,095 gal	SCT-4905-LVR	49.5'	24.7'	17.71'	7.00'	24.71'
301,074 gal	SCT-4906-LVR	49.5'	24.7'	21.25'	7.00'	28.25'
352,053 gal	SCT-4907-LVR	49.5'	24.7'	24.79'	7.00'	31.79'
403,031 gal	SCT-4908-LVR	49.5'	24.7'	28.33'	7.00'	35.33'

Corrugated Steel Water Tanks

Specifications

Corrugated Tank - 30° V Rib Roof

Capacity	Model	Diameter	Radius	Eave Height	Roof Height	Total Height
2,886 gal	SCT-I201-VR	12.4'	6.2'	3.54'	3.25'	6.79'
4,510 gal	SCT-I501-VR	15.5'	7.7'	3.54'	4.17'	7.71'
6,072 gal	SCT-I202-VR	12.4'	6.2'	7.08'	3.25'	10.33'
6,494 gal	SCT-I801-VR	18.6'	9.3'	3.54'	5.08'	8.62'
8,839 gal	SCT-2101-VR	21.7'	10.8'	3.54'	6.00'	9.54'
9,259 gal	SCT-I203-VR	12.4'	6.2'	10.63'	3.25'	13.88'
9,488 gal	SCT-I502-VR	15.5'	7.7'	7.08'	4.17'	11.25'
11,545 gal	SCT-2401-VR	24.7'	12.4'	3.54'	6.92'	10.46'
12,445 gal	SCT-I204-VR	12.4'	6.2'	14.17'	3.25'	17.42'
13,663 gal	SCT-I802-VR	18.6'	9.3'	7.08'	5.08'	12.16'
14,467 gal	SCT-I503-VR	15.5'	7.7'	10.63'	4.17'	14.80'
14,612 gal	SCT-2701-VR	27.8'	13.9'	3.54'	7.75'	11.29'
15,631 gal	SCT-I205-VR	12.4'	6.2'	17.71'	3.25'	20.96'
18,597 gal	SCT-2102-VR	21.7'	10.8'	7.08'	6.00'	13.08'
18,039 gal	SCT-3001-VR	30.9'	15.5'	3.54'	8.67'	12.21'
18,817 gal	SCT-I206-VR	12.4'	6.2'	21.25'	3.25'	24.50'
19,445 gal	SCT-I504-VR	15.5'	7.7'	14.17'	4.17'	18.34'
20,832 gal	SCT-I803-VR	18.6'	9.3'	10.63'	5.08'	15.71'
21,828 gal	SCT-3401-VR	34.0'	17.0'	3.54'	9.58'	13.12'
24,290 gal	SCT-2402-VR	24.7'	12.4'	7.08'	6.92'	14.00'
24,423 gal	SCT-I505-VR	15.5'	7.7'	17.71'	4.17'	21.88'
25,977 gal	SCT-3701-VR	37.1'	18.6'	3.54'	10.75'	14.29'
28,001 gal	SCT-I804-VR	18.6'	9.3'	14.17'	5.08'	19.25'
28,355 gal	SCT-2103-VR	21.7'	10.8'	10.3	6.00'	16.63'
29,402 gal	SCT-I506-VR	15.5'	7.5'	21.25'	4.17'	25.42'
30,742 gal	SCT-2702-VR	27.8'	13.9'	7.08'	7.75'	14.83'
35,170 gal	SCT-I805-VR	18.6'	9.3'	17.71'	5.08'	22.79'
35,357 gal	SCT-4301-VR	43.3'	21.7'	3.54'	12.92'	16.46'
37,035 gal	SCT-2403-VR	24.7'	12.4'	10.63'	6.92'	17.55'
37,953 gal	SCT-3002-VR	30.9'	15.5'	7.08'	8.67'	15.75'
38,112 gal	SCT-2104-VR	21.7'	10.8'	14.17	6.00'	20.17'
42,339 gal	SCT-I806-VR	18.6'	9.3'	21.25'	5.08'	26.33'
45,923 gal	SCT-3402-VR	34.0'	17.0'	7.08'	9.58'	16.66'

Corrugated Steel Water Tanks

Specifications

46,181 gal	SCT-4901-VR	49.5'	24.7'	3.54'	14.67'	18.21'
46,872 gal	SCT-2703-VR	27.8'	13.9'	10.63'	7.75'	18.38'
47,870 gal	SCT-2105-VR	21.7'	10.8'	17.71'	6.00'	23.71'
49,779 gal	SCT-2404-VR	24.7'	12.4'	14.17'	6.92'	21.09'
54,652 gal	SCT-3702-VR	37.1'	18.6'	7.08'	10.75'	17.83'
57,627 gal	SCT-2106-VR	21.7'	10.8'	21.25'	6.00'	27.25'
57,866 gal	SCT-3003-VR	30.9'	15.5'	10.63'	8.67'	19.30'
62,524 gal	SCT-2405-VR	24.7'	12.4'	17.71'	6.92'	24.63'
63,002 gal	SCT-2704-VR	27.8'	13.9'	14.17'	7.75'	21.92'
70,018 gal	SCT-3403-VR	34.0'	17.0'	10.63'	9.58'	20.20'
74,388 gal	SCT-4302-VR	43.3'	21.7'	7.08'	12.92'	20.00'
75,268 gal	SCT-2406-VR	24.7'	12.4'	21.25'	6.92'	28.17'
77,780 gal	SCT-3004-VR	30.9'	15.5'	14.17'	8.67'	22.84'
79,132 gal	SCT-2705-VR	27.8'	13.9'	17.71'	7.75'	25.46'
83,328 gal	SCT-3703-VR	37.1'	18.6'	10.63'	10.75'	21.38'
95,262 gal	SCT-2706-VR	27.8'	13.9'	21.25'	7.75'	29.00'
97,693 gal	SCT-3005-VR	30.9'	15.5'	17.71'	8.67'	26.38'
94,114 gal	SCT-3404-VR	34.0'	17.0'	14.17'	9.58'	23.75'
97,159 gal	SCT-4902-VR	49.5'	24.7'	7.08'	14.67'	21.75'
112,003 gal	SCT-3704-VR	37.1'	18.6'	14.17'	10.75'	24.92'
113,418 gal	SCT-4303-VR	43.3'	21.7'	10.63'	12.92'	23.55'
117,607 gal	SCT-3006-VR	30.9'	15.5'	21.25'	8.67'	29.92'
118,209 gal	SCT-3405-VR	34.0'	17.0'	17.71'	9.58'	27.29'
140,679 gal	SCT-3705-VR	37.1'	18.6'	17.71'	10.75'	28.46'
142,304 gal	SCT-3406-VR	34.0'	17.0'	21.25'	9.58'	30.83'
148,138 gal	SCT-4903-VR	49.5'	24.7'	10.63'	14.67'	25.30'
152,449 gal	SCT-4304-VR	43.3'	21.7'	14.17'	12.92'	27.09'
169,354 gal	SCT-3706-VR	37.1'	18.6'	21.25'	10.75'	32.00'
191,479 gal	SCT-4305-VR	43.3'	21.7'	17.71'	12.92'	30.63'
199,117 gal	SCT-4904-VR	49.5'	24.7'	14.17'	14.67'	28.84'
230,510 gal	SCT-4306-VR	43.3'	21.7'	21.25'	12.92'	34.17'
250,095 gal	SCT-4905-VR	49.5'	24.7'	17.71'	14.67'	32.38'
301,074 gal	SCT-4906-VR	49.5'	24.7'	21.25'	14.67'	35.92'
352,053 gal	SCT-4907-VR	49.5'	24.7'	24.79'	14.67'	39.46'
403,031 gal	SCT-4908-VR	49.5'	24.7'	28.33'	14.67'	43.00'

Corrugated Steel Water Tanks

Specifications

Corrugated Tank - 30° Low J Rib Roof

Capacity	Model	Diameter	Radius	Eave Height	Roof Height	Total Height
25,977 gal	SCT-3701-LJR	37.1'	18.6'	3.54'		7.46'
58,447 gal	SCT-5501-LJR	55.7'	27.8'	3.54'	6.00'	9.54'
54,652 gal	SCT-3702-LJR	37.1'	18.6'	7.08'		12.21'
83,328 gal	SCT-3703-LJR	37.1'	18.6'	10.63'		16.26'
87,417 gal	SCT-6801-LJR	68.1'	34.1'	3.54'	9.00'	12.54'
103,905 gal	SCT-7401-LJR	74.2'	37.1'	3.54'	10.15'	13.69'
112,003 gal	SCT-3704-LJR	37.1'	18.6'	14.17'		18.08'
122,967 gal	SCT-5502-LJR	55.7'	27.8'	7.08'	6.00'	13.08'
140,679 gal	SCT-3705-LJR	37.1'	18.6'	17.71'		21.63'
169,354 gal	SCT-3706-LJR	37.1'	18.6'	21.25'		24.75'
183,916 gal	SCT-6802-LJR	68.1'	34.1'	7.08'	9.00'	16.08'
187,487 gal	SCT-5503-LJR	55.7'	27.8'	10.63'	6.00'	16.63'
218,605 gal	SCT-7402-LJR	74.2'	37.1'	7.08'	10.15'	17.23'
252,007 gal	SCT-5504-LJR	55.7'	27.8'	14.17'	6.00'	20.17'
280,415 gal	SCT-6803-LJR	68.1'	34.1'	10.63'	9.00'	19.63'
316,527 gal	SCT-5505-LJR	55.7'	27.8'	17.71'	6.00'	23.71'
333,305 gal	SCT-7403-LJR	74.2'	37.1'	10.63'	10.15'	20.77'
376,914 gal	SCT-6804-LJR	68.1'	34.1'	14.17'	9.00'	23.17'
381,047 gal	SCT-5506-LJR	55.7'	27.8'	21.25'	6.00'	27.25'
445,567 gal	SCT-5507-LJR	55.7'	27.8'	24.79'	6.00'	30.79'
448,005 gal	SCT-7404-LJR	74.2'	37.1'	14.17'	10.15'	24.32'
473,414 gal	SCT-6805-LJR	68.1'	34.1'	17.71'	9.00'	26.71'
510,086 gal	SCT-5508-LJR	55.7'	27.8'	28.33'	6.00'	34.33'
562,705 gal	SCT-7405-LJR	74.2'	37.1'	17.71'	10.15'	27.86'
569,913 gal	SCT-6806-LJR	68.1'	34.1'	21.25'	9.00'	30.25'
574,606 gal	SCT-5509-LJR	55.7'	27.8'	31.87'	6.00'	37.87'
639,126 gal	SCT-5510-LJR	55.7'	27.8'	35.42'	6.00'	41.42'
666,412 gal	SCT-6807-LJR	68.1'	34.1'	24.79'	9.00'	33.79'
762,911 gal	SCT-6808-LJR	68.1'	34.1'	28.33'	9.00'	37.33'
792,105 gal	SCT-7407-LJR	74.2'	37.1'	21.25'	10.15'	31.40'
859,410 gal	SCT-6809-LJR	68.1'	34.1'	31.87'	9.00'	40.87'
955,910 gal	SCT-6810-LJR	68.1'	34.1'	35.42'	9.00'	44.42'

Corrugated Steel Water Tanks

Specifications

Corrugated Tank - 30° J Rib Roof

Capacity	Model	Diameter	Radius	Eave Height	Roof Height	Total Height
72,157 gal	SCT-6101-JR	61.9'	30.9'	3.54'	16.75'	20.29'
103,905 gal	SCT-7401-JR	74.2'	37.1'	3.54'	20.33	23.87'
151,812 gal	SCT-6102-JR	61.9'	30.9'	7.08'	16.75'	23.83'
187,487 gal	SCT-5503-JR	55.7'	27.8'	10.63'	15.00'	25.63'
218,605 gal	SCT-7402-JR	74.2'	37.1'	7.08'	20.33	27.41'
231,466 gal	SCT-6103-JR	61.9'	30.9'	10.63'	16.75'	27.38'
252,007 gal	SCT-5504-JR	55.7'	27.8'	14.17'	15.00'	29.17'
311,120 gal	SCT-6104-JR	61.9'	30.9'	14.17'	16.75'	30.92'
316,527 gal	SCT-5505-JR	55.7'	27.8'	17.71'	15.00'	32.71'
333,305 gal	SCT-7403-JR	74.2'	37.1'	10.63'	20.33	30.95'
381,047 gal	SCT-5506-JR	55.7'	27.8'	21.25'	15.00'	36.25'
390,774 gal	SCT-6105-JR	61.9'	30.9'	17.71'	16.75'	34.46'
445,567 gal	SCT-5507-JR	55.7'	27.8'	24.79'	15.00'	39.79'
448,005 gal	SCT-7404-JR	74.2'	37.1'	14.17'	20.33	34.50'
470,428 gal	SCT-6106-JR	61.9'	30.9'	21.25'	16.75'	38.00'
510,086 gal	SCT-5508-JR	55.7'	27.8'	28.33'	15.00'	43.33'
550,082 gal	SCT-6107-JR	61.9'	30.9'	24.79'	16.75'	41.54'
562,705 gal	SCT-7405-JR	74.2'	37.1'	17.71'	20.33	38.04'
574,576 gal	SCT-5509-JR	55.7'	27.8'	31.87'	15.00'	46.87'
629,736 gal	SCT-6108-JR	61.9'	30.9'	28.33'	16.75'	45.08
639,065 gal	SCT-5510-JR	55.7'	27.8'	35.41'	15.00'	50.41'
677,405 gal	SCT-7406-JR	74.2'	37.1'	21.25'	20.33	41.58'
709,391 gal	SCT-6109-JR	61.9'	30.9'	31.87'	16.75'	48.62'
789,045 gal	SCT-6110-JR	61.9'	30.9'	35.42'	16.75'	52.17'
792,105 gal	SCT-7407-JR	74.2'	37.1'	24.79'	20.33	45.12'
906,806 gal	SCT-7408-JR	74.2'	37.1'	28.33'	20.33	48.66'
1,021,506 gal	SCT-7409-JR	74.2'	37.1'	31.87'	20.33	52.20'
1,136,206 gal	SCT-7410-JR	74.2'	37.1'	35.42'	20.33	55.75'

We are here to serve you. Just call or email with your project specifications and details, and we'll do the rest. Our goal is to provide the best solution for your project, with materials delivered on time at a price that fits nicely within your budget.

Our Websites:

www.collapsiblepillowtank.com
www.firesuppressiontank.com
www.water-storage-containers.com
www.erosioncontrol-products.com
www.plastic-watertanks.com
www.water-storage-tank.com